



LAMELLA

ENGINEERED TIMBERS

TECHNICAL DATA SHEET

	14/2	15mm	Native	Herringbone
Timber Origins	European Oak	European Oak	Australian Species	European Oak
Board Style	Plank	Plank	Plank	Herringbone
Thickness / Layer	14 / 2mm	15 / 4mm	15 / 3mm	15 / 3mm
Board Size (mm)	1900 x 190	2200 x 220	1900 x 190	600 x 125
Locking System	Tongue & Groove	Tongue & Groove	Tongue & Groove	Tongue & Groove
Finish	Matte Brushed	Matte Brushed	Matte	Matte Brushed
Grade	ABCD	ABCD	ABCD	ABC
Sqm/ Box	2.166m ²	2.904m ²	2.166m ²	1.2m ²
Pieces / Box	6	6	6	16
Weight / Box	19.71kg	28.31kg	21.12kg	11.70kg
Packaging Size (mm)	1920 x 200 x 90	2220 x 230 x 96	1920 x 200 x 96	620 x 260 x 126
Box / Pallet	50	50		

PRODUCT SUMMARY

Wear Layer	UV Cured Polyurethane Aluminium Oxide coating
Core Structure	Plantation Eucalyptus/Birch, multi cross plywood
Base Layer	Birchwood veneer backing for extra stability
Finish	Matte Brushed
Edge Profile	0.5mm Micro Bevelled Edges
Installation Method	Floating & Direct Stick
Wear Resistance	≥500 circles (S33 sand paper) ASTM D4060
Gloss Level	6°-8°
Moisture Content	6%-9%
Topcoat Adhesion	4B ASTM D3359
Formaldehyde Emission	CARB Phase One ≤0.08 ppm ASTM E1333
Fire Test Report	AS ISO 9239.1-2003
Slip Classification	P3
Acoustic Results	Available upon request
Subfloor Tolerance	Maximum of 3mm variance over 3m
Suitable Application	Residential & Commercial

Durability

Up to 7 coats
UV-hardened
surface finish,
consisting of
polyurethane
and aluminum
oxide

Wearability

Up to 6mm top
layer in solid wood.

Stability

Multiple cross
plywood layers.



WARRANTY



NATIONAL SELECT
FLOORS

02 7229 7323

info@nationalselectfloors.com.au

Building B/6 Carter Street, Lidcombe NSW 2141

www.nationalselectfloors.com.au