



SPECIFICATION DATA SHEET

Experience the elegance of European Oak without compromise. Our 14/2 range has been meticulously engineered to combine refined craftsmanship, lasting durability, and accessible pricing; making luxury flooring attainable for every home.

Each sustainably sourced plank is enhanced with a light wire-brushed matte finish that highlights the oak's natural beauty and texture. Multiple layers of advanced UV cured lacquer provide superior resistance to stains and fading, ensuring your floor maintains its flawless appearance with minimal upkeep.

Available in a curated selection of timeless colours, this range delivers sophistication, comfort, and enduring style; all at a price designed to fit your lifestyle.

Product Details

Style Plank
Timber Origins European Oak
Thickness / Wear Layer 14 / 2 mm
Board Size 1900 x 190 mm
Edge Profile Micro Bevelled
Fitting System Tongue & Groove
Installation Method Floating | Glue Down

Sqm/Box 2.166 m²

Pieces / Box 6 rows includes < 20% nested

Box / Pallet 50 Weight / Box 19.71 kg

Suitable Application Residential & Commercial

Performance & Safety Testing

Slip (AS 4586-2013) P3 (SRV 39) Fire (AS ISO 9239.1-2003) 5 kW/m2

Acoustic Outcome L'nTw 37 (Homestead 5 mm rubber)

AAAC Rating 6 Star

Reports are available upon request.



Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

Technical Summary

Grading ABCD

Top Layer UV Cured Polyurethane Aluminium Oxide Coating

Surface Pre-finished Matte Lacquer
Finish Light Wire Brushed Texture

Core Structure Plantation Eucalyptus/Birch Multi Cross Plywood

Backing Layer Birchwood Veneer for extra stability

Topcoat Adhesion 4B | ASTM D3359

Wear Resistance ≥500 circles (S33 sand paper) | ASTM D4060

Moisture Content6-9%Gloss Level6-8°Density750 kg/m3Janka Hardness Rating5.5-6.0 kN

Formaldehyde Emission CARB Phase One ≤0.08 ppm | ASTM E1333
Environmental Sourced from sustainable managed resources



This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or guarantees.

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.