





SPECIFICATION DATA SHEET

The 15mm range represents the pinnacle of our Lamella Engineered Timbers. A statement of scale, sophistication, and timeless appeal, this larger format creates a seamless flow through interior spaces, enhancing natural light and delivering a sense of grandeur that elevates any design.

Expertly engineered with a 15 mm construction, this range combines architectural presence with enduring stability. The matte brushed finish highlights the natural character of European Oak, while advanced UV cured lacquer layers protect against everyday stains and fading. The result is a floor that retains its flawless appearance with minimal upkeep, year after year.

Offered in an exclusive palette of contemporary décors, the 15mm range embodies premium craftsmanship, exceptional durability, and accessible luxury; designed to transform living spaces into refined environments.

Product Details

Style Plank
Timber Origins European Oak
Thickness / Wear Layer 15 / 4 mm
Board Size 2200 x 260 mm
Edge Profile Micro Bevelled
Fitting System Tongue & Groove

Installation Method Floating | Glue Down | Nail

Sqm/Box 2.904 m

Pieces / Box 6 rows includes < 20% nested

Box / Pallet 50 Weight / Box 28.31 kg

Suitable Application Residential & Commercial

Performance & Safety Testing

Slip (AS 4586-2013) P3 (SRV 39) **Fire (AS ISO 9239.1-2003)** 3.9 kW/m2

Acoustic Outcome L'nTw 40 (Homestead 5 mm rubber)

AAAC Rating 6 Star Reports are available upon request.

Caldu Serein Wvn Auer LET-1502 LET-1501 LET-1503 LET-1504 Maes Fika Laine Ricci LET-1505 LET-1506 LET-1507 LET-1508 Kohle Toska LET-1509 LET-1510

Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

Technical Summary

Grading ABCD

Top Layer UV Cured Polyurethane Aluminium Oxide Coating

Surface Pre-finished Matte Lacquer
Finish Light Wire Brushed Texture

Core Structure Plantation Eucalyptus/Birch Multi Cross Plywood

Backing Layer Birchwood Veneer for extra stability

Topcoat Adhesion 4B | ASTM D3359

Wear Resistance ≥500 circles (S33 sand paper) | ASTM D4060

Moisture Content6-9%Gloss Level6-8°Density754 kg/m3Janka Hardness Rating5.5-6.0 kN

Formaldehyde Emission CARB Phase One ≤0.08 ppm | ASTM E1333

Environmental Sourced from sustainable managed resources



This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or guarantees.

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.