





## SPECIFICATION DATA SHEET

The Herringbone range embodies timeless design and refined craftsmanship, bringing heritage-inspired beauty into modern living spaces. Crafted from sustainably sourced European Oak and select native Australian hardwoods, each piece showcases the natural elegance, strength, and character of genuine timber.

With its classic pattern, the Herringbone design introduces depth, movement, and sophistication, making it the perfect choice for hallways, living areas, and bedrooms. The result is a floor that exudes a high end, architectural feel while retaining warmth and

Finished with subtle matte brushing to enhance natural texture, and protected by multiple layers of UV cured lacquer, the Herringbone range is designed to resist everyday stains and fading. This ensures your floor will retain its flawless elegance for years to come, with minimal upkeep.

## **Product Details**

Herringbone **Style** 

European Oak / Australian Species **Timber Origins** 

Thickness / Wear Layer 15 / 3mm **Board Size** 600 x 125 mm **Edge Profile** Micro Bevelled **Fitting System** Tongue & Groove Installation Method Glue Down only

Sqm/Box Pieces / Box 16 11.7 kg Weight / Box

**Suitable Application** Residential & Commercial

## Performance & Safety Testing

Slip (AS 4586-2013) P3 (SRV 36) Fire (AS ISO 9239.1-2003) 3 kW/m2

L'nTw 38 (Homestead 5 mm rubber) **Acoustic Outcome** 

**AAAC Ratina** 6 Star

Reports are available upon request.



Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

## **Technical Summary**

Grading

UV Cured Polyurethane Aluminium Oxide Coating **Top Laver** 

Surface Pre-finished Matte Lacquer **Finish** Light Wire Brushed Texture

Plantation Eucalyptus/Birch Multi Cross Plywood **Core Structure** 

Birchwood Veneer for extra stability **Backing Layer** 


**Topcoat Adhesion** 4B LASTM D3359

**Wear Resistance** ≥500 circles (S33 sand paper) | ASTM D4060

6-9% **Moisture Content Gloss Level** 6-8° Density 750 kg/m3 Janka Hardness Rating 5.5-6.0 kN

Formaldehvde Emission CARB Phase One ≤0.08 ppm | ASTM E1333 Sourced from sustainable managed resources **Environmental** 





This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.