

SPECIFICATION DATA SHEET

The Natives range is a tribute to the enduring beauty of Australian hardwoods, engineered to embody timeless luxury with an understated elegance that lasts for generations. Featuring a 3 mm premium wear layer of authentic native species, it captures the classic appeal of natural timber while delivering exceptional durability.

Sustainably sourced from Australia's finest hardwoods, each plank radiates warmth, character, and strength, ensuring a product that is as résponsible as it is refined.

The subtle matte brushing enhances the natural grain and texture, while multiple layers of UV cured lacquer provide advanced protection against stains and fading. Designed for longevity with minimal upkeep, the Natives range offers a floor that will remain as elegant and flawless as the day it was laid.

Product Details

Timber Origins Australian Species Thickness / Wear Layer 15 / 3 mm **Board Size** 1900 x 190 mm **Edge Profile** Micro Bevelled **Fitting System** Tongue & Groove

Installation Method Floating | Glue Down | Nail

Sam/Box 2.166 m²

Pieces / Box 6 rows includes <20% nested

Box / Pallet 50 21.12 kg Weight / Box

Suitable Application Residential & Commercial

Performance & Safety Testing

Slip (AS 4586-2013) P3 (SRV 36) Fire (AS ISO 9239.1-2003) 3 kW/m2

Acoustic Outcome L'nTw 38 (Homestead 5 mm rubber)

AAAC Rating 6 Star

Reports are available upon request.















Spotted Gum LET-1512

Images are for general illustration only. Actual product colours may differ due to variations in screen displays or printing processes. The scale of the images does not reflect true colour variation. For an accurate representation, please refer to physical samples. Images are not legally binding.

Technical Summary

Grading ARCD

UV Cured Polyurethane Aluminium Oxide Coating **Top Laver**

Surface Pre-finished Matte Lacquer

Finish Brushed Texture

Plantation Eucalyptus/Birch Multi Cross Plywood **Core Structure**

Backing Layer Birchwood Veneer for extra stability

Topcoat Adhesion 4B LASTM D3359

Wear Resistance ≥500 circles (S33 sand paper) | ASTM D4060

6-9% **Moisture Content Gloss Level** 6-8° Density 750 kg/m3 Janka Hardness Rating 5.5-6.0 kN

Formaldehvde Emission CARB Phase One ≤0.08 ppm | ASTM E1333 Sourced from sustainable managed resources **Environmental**

Durability 7 coats Wearability **UV-hardened** Stability surface finish. 3 mm top consisting of layer in solid wood Multiple cross polyurethane plywood layers. and aluminum

This specification data sheet has been prepared by National Select Floors. All information provided was accurate at the time of writing and publication. National Select Floors reserves the right to alter product details at any time without prior notification. Images included are for illustrative purposes only and do not confer any rights or

National Select Floors recommends installation by a professional flooring contractor or skilled tradesperson and must follow the Australian Standards for flooring installations. All installations must also be performed in accordance with National Select Floors installation guidelines. If you have any concerns regarding the installation process, please contact your reseller.

Installation guidelines and Warranty information are available from our website.